

Grinding wheels

Performance Line SG ★★☆☆



SG STEEL ★★☆☆

Grinding wheel for steel with high grinding performance and very long tool life.

Advantages:

- Fast work progress and maximum economic efficiency thanks to the high grinding performance.
- Fewer tool changes due to the very long tool life.

Materials that can be worked:
steel

Applications:



surface grinding, weld dressing, work on fillet welds, grouting, chamfering, deburring

Abrasive:

Special aluminium oxide A

Recommendations for use:

- Width of 4.1 mm is ideal for work on root seams.

D [mm]	U [mm]	EAN 4007220	*	H [mm]	Max. RPM		Description
Depressed-centre type E (shape 27) 							
70	6.3	471067	*	10.0	21,800	10	E 70-6 SG STEEL/10,0
76	6.3	471081	*	10.0	20,200	10	E 76-6 SG STEEL/10,0
100	4.1	471104	-	16.0	15,300	10	E 100-4,1 SG STEEL/16,0
	6.3	471111	-	16.0	15,300	10	E 100-6 SG STEEL/16,0
115	4.1	640845	-	22.23	13,300	10	E 115-4,1 SG STEEL
	7.2	468944	-	22.23	13,300	10	E 115-7 SG STEEL
125	4.1	457696	-	22.23	12,200	10	E 125-4,1 SG STEEL
	7.2	468951	-	22.23	12,200	10	E 125-7 SG STEEL
150	4.1	529225	-	22.23	10,200	10	E 150-4,1 SG STEEL
	7.2	640791	-	22.23	10,200	10	E 150-7 SG STEEL
180	4.1	478752	-	22.23	8,500	10	E 180-4,1 SG STEEL
	7.2	470145	-	22.23	8,500	10	E 180-7 SG STEEL
	8.3	470152	-	22.23	8,500	10	E 180-8 SG STEEL
230	7.2	470169	-	22.23	6,600	10	E 230-7 SG STEEL
	8.3	470176	-	22.23	6,600	10	E 230-8 SG STEEL

* Also suitable for stainless steel (INOX).

